



PANEL HEIGHT:
 "A": _____ in
 MAXIMUM 120"

WALL LENGTH:
 "B": _____ lft

BOTTOM CLOSURE:
 _____ lft
 OPTIONAL 2-PIECE:

ACCESSORIES:
 INSIDE CORNER:
 OUTSIDE CORNER:

ALUMINUM		GALVANIZED STEEL	COPPER		PRE-WEATHERED ZINC
<input type="checkbox"/> .032"	<input type="checkbox"/> .040"	24GA <input type="checkbox"/>	16oz <input type="checkbox"/>	20oz <input type="checkbox"/>	<input type="checkbox"/> .8mm <input type="checkbox"/> 1.0mm
BAKED ENAMEL COLOR: _____		KYNAR® COLOR: _____	COLD ROLLED: <input type="checkbox"/>	STAINLESS STEEL	
MILL FINISH: <input type="checkbox"/>			LEAD COATED: <input type="checkbox"/>	.018" (26GA) <input type="checkbox"/>	
KYNAR® COLOR: _____			ZINC-COATED: <input type="checkbox"/>	#2D FINISH <input type="checkbox"/>	

Contractor: _____

Job Name: _____

Signature: _____

76-11 88th Street
 Glendale, NY 11385
 [P] 718-846-0400
 [F] 718-846-7803
 [E] info@litsco.com

Streamline® Metal Panel
 Exposed fastener corrugated wall panel
 DON'T FORGET **LOCK-TIGHT COPING** OR
FASCIA FOR A COMPLETE SYSTEM

